

Main Street Stonely

Details of Brickwork as Required by Condition 4 of 22/00793/FUL & Condition 6 of 22/00794/LBC

Cook & Cook Consultancy

New Brickwork for Existing Listed Building

Brickwork to the extensions of the listed building will be built using a locally sourced reclaimed brick as recommended by the Conservation Officer.

The measurements of the reclaimed brick match the existing. They will be laid in Flemish bond with a 6:1 mix of cavenham soft sand and white cement.

The brickwork will then be painted in an external breathable white masonry paint to match the existing dwelling.



Image A: Reclaimed brick to be used unpainted



Image B: Reclaimed brick panel painted in external breathable white masonry paint

COOK & COOK

New Brickwork for New Dwelling

Brickwork to the new dwelling, garages and garden wall will be built using a TBS Original Gault Blend as recommended by the Conservation Officer.

The brick will be laid in a stretcher bond using a 6:1 mix of cavenham soft sand and white cement.



Image C: TBS Original Gault Blend sample panel on site



Image D: TBS Original Gault Blend used on another project

Existing Brickwork

Existing brickwork will be cleaned and made good.

External breathable masonry paint will then be applied to the brickwork.

The colour proposed is white to match existing.



Image E: Existing white painted brickwork to existing building

COOK & COOK