Envirograf®
Protecting the irreplaceable

CV RANGE

Innovators - Developers - Manufacturers
Passive Fire Prevention Products

IMPORTANT INFORMATION - CV RANGE

TO ALL INSTALLERS:
PLEASE TAKE NOTE OF ALL OF THE INSTRUCTIONS BELOW





Depending on which size CV Cavity Strip Barrier you have ordered, they will either need to be mechanically fixed every 300mm or alternatively use the fixing brackets if supplied. **THE CV CAVITY STRIP BARRIER MUST BE FIXED BACK TO THE SUBSTRATE** (e.g. wall or cement board etc). DO NOT FIX the Cavity Strip Barrier to polystyrene or any insulation material. **IT MUST BE FIXED BACK TO THE SUBSTRATE** using the brackets or mechanically fixed every 300mm with a non-combustible fixing.

Should you need to cut the Barrier, please **ensure all joints are sealed with the strips** which are supplied. We can supply more strips if required for a small charge. Should you need to cut the barrier for installation purposes then the barrier must remain continuous without any breaches i.e. full length and height where applicable. Each length should be tightly butted up to the next. **Do not allow any gaps in between each length of barrier**.

If using brackets, use 1½" (38mm) No.8 screws. If not using brackets, use screws, into timber at 250mm - 300mm between centres.